



HUIZHOU ZHANCI HARDWARE PRODUCTS COMPANY LIMITED

DRAGON PRECISION HARDWARE CO., LIMITED

B02 Building Jintaiyuan Industrial Park, Hongtian Village, Xinxu Town, Huiyang Area, Huizhou, Guangdong, China.

TEL:86-186-65104411 FAX:86-752-3629608 Email:alice@clichnuts.com

Stainless steel rivet nuts

FH-RB-SS Flat Head Round Body Plain



Rivet nuts, also known as the rivet nut, pull the cap, securing areas for all types of sheet metal, pipes and other manufacturing industries, widely used in the automotive, aviation, railway, refrigeration, elevators, switches, instruments, furniture, decoration and other electromechanical and light industrial products on the assembly. To solve the sheet metal.

Thread	P/N	T(GRIP RANGE)		A	Hole Size	D	B	K	L
		Min	Max	Ref	0.1 0	0.07 -0.1			
M4*0.7	FH-RB/SS-0420	0.5-2.0		6	6	5.9	8.5±0.25	0.8±0.1	10.5±0.25
M5*0.8	FH-RB/SS-0525	0.5-2.5		7.5	7	6.9	10.0±0.3	1.0±0.15	13.0±0.3
M6*1.0	FH-RB/SS-0630	0.5-3.0		9.2	9	8.9	12.3±0.3	1.3 0.2 -0.05	15.5±0.3
M8*1.25	FH-RB/SS-0835	1.0-3.5		11.5	11	10.9	15.0±0.3	1.5±0.15	18.5±0.3
M10*1.5	FH-RB/SS-1040	1.0-4.0		12.5	13	12.9	17.0±0.3	1.6±0.15	21.0±0.3

FH-RBC-SS Flat Head Round Body Plain Close End



Thread	P/N	T(GRIP RANGE)		A	Hole Size	D	B	K	L
		Min	Max	Ref	0.1	0.07			
					0	-0.1			
M4*0.7	FH-RBC/SS-0420	0.5-2.0		11.3	6	5.9	9.0±0.25	0.8±0.1	16.0±0.25
M5*0.8	FH-RBC/SS-0525	0.5-2.5		13.8	7	6.9	10.0±0.3	1.0±0.15	19.0±0.3
M6*1.0	FH-RBC/SS-0630	0.5-3.0		15	9	8.9	12.3±0.3	1.3 0.2 -0.05	21.0±0.3
M8*1.25	FH-RBC/SS-0835	1.0-3.5		18.2	11	10.9	15.0±0.3	1.5±0.15	25.0±0.3
M10*1.5	FH-RBC/SS-1040	1.0-4.0		19.4	13	12.9	17.0±0.3	1.6±0.15	27.0±0.3

FH-KB-SS Flat Head Knurled Body



Thread	P/N	T(GRIP RANGE)		A	Hole Size	D	B	K	L		
		Min	Max	Ref	0.1	0.07					
					0	-0.1					
M4*0.7	FH-KB/SS-0420	0.5-2.0		6.5	6	5.9	9.0±0.25	0.8±0.1	10.5±0.25		
M5*0.8	FH-KB/SS-0525	0.5-2.5		8	7	6.9	10.0±0.3	1.0±0.15	13.0±0.3		
M6*1.0	FH-KB/SS-0630	0.5-3.0		9.2	9	8.9	12.3±0.3	1.3 <table border="1" style="display: inline-table; vertical-align: middle;"><tr><td>0.2</td></tr><tr><td>-0.05</td></tr></table>	0.2	-0.05	15.5±0.3
0.2											
-0.05											
M8*1.25	FH-KB/SS-0835	1.0-3.5		11.5	11	10.9	14.5±0.3	1.5±0.15	18.5±0.3		
M10*1.5	FH-KB/SS-1040	1.0-4.0		13.5	13	12.9	17.0±0.3	1.6±0.15	21.0±0.3		

FH-KBC-SS Flat Head Knurled Body Close End



Thread	P/N	T(GRIP RANGE)		A	Hole Size	D	B	K	L
		Min	Max	Ref	0.1	0.07			
					0	-0.1			
M4*0.7	FH-KBC/SS-0420	0.5-2.0		11.8	6	5.9	9.0±0.25	0.8±0.1	16.0±0.25
M5*0.8	FH-KBC/SS-0525	0.5-2.5		12	7	6.9	10.0±0.3	1.0±0.15	17.0±0.3
M6*1.0	FH-KBC/SS-0630	0.5-3.0		12.7	9	8.9	12.3±0.3	1.3	19.2±0.3
M8*1.25	FH-KBC/SS-0835	1.0-3.5		14.2	11	10.9	15.0±0.3	1.5±0.15	21.5±0.3
M10*1.5	FH-KBC/SS-1040	1.0-4.0		18	13	12.9	17.0±0.3	1.6±0.15	27.0±0.35

RH-RB-SS Reduce Head Round Body Plain



Thread	P/N	T(GRIP RANGE)		A	Hole Size		D	B	K	L
		Min	Max	Ref	0.1	0.07				
					0	-0.1				
M4*0.7	RH-RB/SS-0420	0.5-2.0		6.5	6	5.9	7	0.2	0.5±0.1	10.5±0.25
								-0.1		
M5*0.8	RH-RB/SS-0520	0.5-2.0		7	7	6.9	8	0.25	0.5±0.1	11.5±0.25
								-0.1		
M6*1.0	RH-RB/SS-0625	0.5-2.5		8.5	9	8.9	10	0.25	0.6±0.15	14.0±0.3
								-0.1		
M8*1.25	RH-RB/SS-0830	0.5-3.0		10.5	11	10.9	12	0.25	0.65±0.15	16.5±0.3
								-0.1		
M10*1.5	RH-RB/SS-1035	1.0-3.5		11.5	13	12.9	14	0.35	0.7±0.15	17.7±0.3

RH-RBC-SS Reduce Head Round Body Plain Close



Thread	P/N	T(GRIP RANGE)		A	Hole Size	D	B	K	L	
		Min	Max	Ref	0.1	0.07				
					0	-0.1				
M4*0.7	RH-RBC/SS-0420	0.5-2.0		11	6	5.9	7	0.2 -0.1	0.5±0.1	15.0±0.25
M5*0.8	RH-RBC/SS-0520	0.5-2.0		12.5	7	6.9	8	0.25 -0.1	0.5±0.1	16.5±0.25
M6*1.0	RH-RBC/SS-0625	0.5-2.5		15.5	9	8.9	10	0.25 -0.1	0.6±0.15	20.5±0.3
M8*1.25	RH-RBC/SS-0830	0.5-3.0		17.6	11	10.9	12	0.25 -0.1	0.65±0.15	23.0±0.3
M10*1.5	RH-RBC/SS-1035	1.0-3.5		18.3	13	12.9	14	0.35 -0.1	0.7±0.15	24.5±0.3

RH-KB-SS Reduce Head Knurled Body



Thread	P/N	T(GRIP RANGE)		A	Hole Size	D	B	K	L
		Min	Max	Ref	0.1	0.07			
					0	-0.1			
M4*0.7	RH-KB/SS-0420	0.5-2.0		6.5	6	5.9	7	0.5±0.1	10.5±0.25
								-0.1	
M5*0.8	RH-KB/SS-0520	0.5-2.0		7.2	7	6.9	8	0.5±0.1	11.5±0.25
								-0.1	
M6*1.0	RH-KB/SS-0625	0.5-2.5		8.7	9	8.9	10	0.6±0.15	14.0±0.3
								-0.1	
M8*1.25	RH-KB/SS-0830	0.5-3.0		10.5	11	10.9	12	0.65±0.15	16.5±0.3
								-0.1	
M10*1.5	RH-KB/SS-1035	1.0-3.5		10.7	13	12.9	14	0.7±0.15	17.7±0.3
								-0.1	

RH-KBC-SS Reduce Head Knurled Body Close End



Thread	P/N	T(GRIP RANGE)		A	Hole Size		B	K	L	
		Min	Max	Ref	0.1	0.07				
					0	-0.1				
M4*0.7	RH-KBC/SS-0420	0.5-2.0		11.2	6	5.9	7	0.2 -0.1	0.5±0.1	15.0±0.25
M5*0.8	RH-KBC/SS-0520	0.5-2.0		11.5	7	6.9	8	0.25 -0.1	0.5±0.1	16.5±0.25
M6*1.0	RH-KBC/SS-0625	0.5-2.5		15	9	8.9	10	0.25 -0.1	0.6±0.15	20.5±0.3
M8*1.25	RH-KBC/SS-0830	0.5-3.0		17.5	11	10.9	12	0.25 -0.1	0.65±0.15	23.0±0.3
M10*1.5	RH-KBC/SS-1035	1.0-3.5		18	13	12.9	14	0.35 -0.1	0.7±0.15	24.5±0.3

CH-RB-SS Countersunk Head Round Body Plain



Thread	P/N	T(GRIP RANGE)		A	Hole Size		B	K	L
		Min	Max	Ref	0.1	0.07	±0.3	±0.15	±0.3
M4*0.7	CH-RB/SS-0430	1.5-3.0		7.5	6	5.9			
M5*0.8	CH-RB/SS-0535	1.5-3.5		7.8	7	6.9	10	1.5	13
M6*1.0	CH-RB/SS-0640	1.5-4.0		9	9	8.9	12	1.5	15.5
M8*1.25	CH-RB/SS-0845	2.0-4.5		12	11	10.9	14	1.5	18.5
M10*1.5	CH-RB/SS-1050	2.0-5.0		13	13	12.9	16	1.5	21

CH-KB-SS Countersunk Head Knurled Body



Thread	P/N	T(GRIP RANGE)		A	Hole Size	D	B	K	L
		Min	Max	Ref	0.1	0.07	±0.3	±0.15	±0.3
					0	-0.1			
M4*0.7	CH-KB/SS-0430	1.5-3.0		7.5	6	5.9	9	1.5	12
M5*0.8	CH-KB/SS-0535	1.5-3.5		7.8	7	6.9	10	1.5	13
M6*1.0	CH-KB/SS-0640	1.5-4.0		9	9	8.9	12	1.5	15.5
M8*1.25	CH-KB/SS-0845	2.0-4.5		12	11	10.9	14	1.5	18.5
M10*1.5	CH-KB/SS-1050	2.0-5.0		13	13	12.9	16	1.5	21

RHH-IHB-SS Reduce Hex Head Inner-Hex Body



Thread	P/N	T(GRIP RANGE)		A	Hole Size	D	HB	
		Min	Max	Ref	0.1 0	0.07 -0.1	0.25 -0.1	0.3 -0.1
M4*0.7	RHH-IHB/SS-0420	0.5-2.0		8	6	5.9	7	
M5*0.8	RHH-IHB/SS-0525	0.5-2.5		8.2	7	6.9	8	
M6*1.0	RHH-IHB/SS-0630	0.5-3.0		10.7	9	8.9	10	
M8*1.25	RHH-IHB/SS-0835	1.0-3.5		11.2	11	10.9	12	
M10*1.5	RHH-IHB/SS-1040	1.0-4.0		13.5	13	12.9	14.5*	

RHH-IHBC-SS Reduce Hex Head Inner-Hex Body Close End



Thread	P/N	T(GRIP RANGE)		A	Hole Size	D	HB	
		Min	Max	Ref	0.1 0	0.07 -0.1	0.25 -0.1	0.3 -0.1
M4*0.7	RHH-IHBC/SS-0420	0.5-2.0		11.5	6	5.9	7	
M5*0.8	RHH-IHBC/SS-0525	0.5-2.5		13.5	7	6.9	8	
M6*1.0	RHH-IHBC/SS-0630	0.5-3.0		15.8	9	8.9	10	
M8*1.25	RHH-IHBC/SS-0835	1.0-3.5		18.2	11	10.9	12	
M10*1.5	RHH-IHBC/SS-1040	1.0-4.0		23.2	13	12.9	14.5	

FH-IHB-SS Flat Head Inner-Hex Body



Thread	P/N	T(GRIP RANGE)		A	Hole Size	D	B	K	L
		Min	Max	Ref	0.1	0.07	±0.3		±0.3
					0	-0.1			
M4*0.7	FH-IHB/SS-0420	0.5-2.0		7.2	6	5.9	9	0.8±0.1	11
M5*0.8	FH-IHB/SS-0525	0.5-2.5		7.5	7	6.9	10	1.0±0.15	12
M6*1.0	FH-IHB/SS-0630	0.5-3.0		9.2	9	8.9	12.7	1.3	15.5
M8*1.25	FH-IHB/SS-0835	1.0-3.5		11	11	10.9	16	1.5±0.15	18
M10*1.5	FH-IHB/SS-1040	1.0-4.0		13.2	13	12.9	18	1.7±0.15	21

FH-IHBC-SS Flat Head Inner-Hex Body Close End



Thread	P/N	T(GRIP RANGE)		A	Hole Size	D	B	K	L
		Min	Max	Ref	0.1 0	0.07 -0.1	±0.3	±0.15(*±0.1)	±0.3(*±0.35)
M4*0.7	FH-IHBC/SS-0420	0.5-2.0		11.5	6	5.9	9	1.0*	16
M5*0.8	FH-IHBC/SS-0525	0.5-2.5		13.5	7	6.9	10	1	18.5
M6*1.0	FH-IHBC/SS-0630	0.5-3.0		17	9	8.9	12.7	1.5	23
M8*1.25	FH-IHBC/SS-0835	1.0-3.5		18.2	11	10.9	16	1.5	25.0*
M10*1.5	FH-IHBC/SS-1040	1.0-4.0		25	13	12.9	19	1.7	33.0*